



户内高压隔离开关 ▶▶▶


GN⁶₈-⁶₁₀型户内三相高压隔离开关

结构

GN6-6、10T型户内三相高压隔离开关由底座、支柱瓷绝缘子、操作瓷绝缘子和导电部分组成。

GN8-6、10T-I、II型户内三相高压隔离开关由底座、支柱瓷绝缘子、瓷套、操作瓷绝缘子和导电部分组成。

GN8-6、10T-III型户内三相高压隔离开关由底座、瓷套、操作瓷绝缘子和导电部分组成。



基本参数

型 号	额定电压 kV	最高工作电压 kV	额定电流 A	动稳定电流 kA (峰值)	5s热稳定电流 kA (有效值)
GN6-6T/200, GN8-6T/200-I、II、III	6	6.9	200	25.5	10
GN6-6T/200, GN8-6T/400-I、II、III	6	6.9	400	40	14
GN6-6T/630, GN8-6T/630-I、II、III	6	6.9	630	52	20
GN6-10T/200, GN8-10T/200-I、II、III	10	11.5	200	25.5	10
GN6-10T/400, GN8-10T/400-I、II、III	10	11.5	400	40	14
GN6-10T/630, GN8-10T/630-I、II、III	10	11.5	630	52	20
GN6-10T/1250, GN8-10T/1250-I、II、III	10	11.5	1250	75	30
GN6-35T-1250	35	40.5	1250	75	30


外型及安装尺寸

型 号	主要尺寸 (mm)					重量 kg
	H	h	L	A1	A	
GN6-6T/200	429	163	750	200	546	25
GN6-6T/400	433	167	750	200	546	26
GN6-6T/630	437	170	750	200	546	27
GN6-10T/200	449	183	850	250	646	28
GN6-10T/400	453	187	850	250	646	29
GN6-10T/630	457	190	850	250	646	31
GN6-10T/1250	515	187	915	250	700	36
GN6-35/1250	1000	480	1590	450	1140	159
GN6-35/1250全工况	1000	480	1590	450	1140	137
GN8-6T/200-I、II、III	600	163	787	200	580	34
GN8-6T/400-I、II、III	610	167	787	200	580	36
GN8-6T/630-I、II、III	615	170	787	200	580	38
GN8-10T/200-I、II、III	640	183	887	250	680	38
GN8-10T/400-I、II、III	650	187	887	250	680	41
GN8-10T/630-I、II、III	655	190	887	250	680	44
GN8-10T/1250-I、II、III	680	187	915	250	700	64





户内高压隔离开关



GN₈₋₁₀⁶⁻⁶型户内三相高压隔离开关




GN6-6T/200, 400, 630
GN6-10T/200, 400, 630 1250型外形尺寸图



GN6-35/1250型外形尺寸图



GN6-6T/200-1, 400-1
GN6-10T/200-1, 400-1, 630-1, 1250-1 型外形尺寸图
(II、III型的高和安装尺寸与I型相同)





抚顺华岳电气制造有限公司

Fushun Huayue Electric Production Co., Ltd.

地址：辽宁省抚顺市新抚区礼泉路2号

邮编：113008

电话：86-413-2439988 8235578

传真：86-413-2423906 8235578

网址：<http://www.fepw.net>

电子邮箱：info@fepw.net