

金属氧化物避雷器 (Y10W2 系列) 主要技术参数 Main Technical Parameters of MOA (Y10W2 Series)

型 号 Type	避雷器 额定电压 kV (有效值)	系统额定 电压 kV (有效值)	避雷器持续 运行电压 kV (有效值)	直流 1mA 参考电压 不小于 kV	波头 1μs 10kA 陡波冲击电流 残压不大于 kV (峰值)	8/20μs 10kA 雷电冲击电流 残压不大于 kV (峰值)	30/60μs 500A 操作冲击电流 残压不大于 kV (峰值)	2000μs 方波通流 容量 18 次 A (峰值)	4/10μs 冲击大电流 2 次 kA (峰值)	爬电 距离 mm Creepage distance mm	
Y10W2-96/250	96	110	75	140	280	250	213	400	100	3780	
Y10W2-96/250N ₂					262	238	202				
Y10W2-96/238	100		78	145	291	260	221				
Y10W2-100/260					273	248	211				
Y10W2-100/248	102		79.6	148	297	266	226				
Y10W2-100/248N ₂					278	253	215				
Y10W2-102/266	108		84	157	315	281	239				
Y10W2-102/266N ₂					295	268	228				
Y10W2-102/253	192		220	150	280	560	500	426		600	7560
Y10W2-102/253N ₂						524	476	404			
Y10W2-108/281	200			156	290	582	520	442			
Y10W2-108/281N ₂						546	496	422			
Y10W2-108/268	204	159		296	594	532	452	800			
Y10W2-108/268N ₂					556	506	430				
Y10W2-192/500	216	168.5		314	630	562	478				
Y10W2-192/500N ₂					590	536	456				
Y10W2-192/476	192	220		150	280	560	500	426	600	7560	
Y10W2-192/476N ₂						524	476	404			
Y10W2-200/520	200			156	290	582	520	442			
Y10W2-200/520N ₂						546	496	422			
Y10W2-200/496	204		159	296	594	532	452	800			
Y10W2-200/496N ₂					556	506	430				
Y10W2-204/532	216		168.5	314	630	562	478				
Y10W2-204/532N ₂					590	536	456				
Y10W2-204/506	216		168.5	314	630	562	478				
Y10W2-204/506N ₂					590	536	456				
Y10W2-216/562	216		168.5	314	630	562	478				
Y10W2-216/562N ₂					590	536	456				
Y10W2-216/536	216	168.5	314	630	562	478					
Y10W2-216/536N ₂				590	536	456					