

金属氧化物避雷器 (YH10W2 系列) 主要技术参数 Main Technical Parameters of MOA(YH10W2 Seyies)

型号 Type	避雷器 额定电压 kV (有效值)	Rated voltage of arrester kV(rms)	系统额定 电压 kV (有效值)	Rated voltage of system kV(rms)	避雷器持续 运行电压 kV (有效值)	Continuous operating voltage of arrester kV(rms)	直流 1mA 参考电压 不小于 kV	DC1mA reference voltage not less than kV	波头 1 μ s 10kA 陡波冲击电流 残压不大于 kV (峰值)	Wave head 1 μ s 10kA steep current impulse residual voltage not more than kV (peak)	8/20 μ s 10kA 雷电冲击电流 残压不大于 kV (峰值)	8/20 μ s 10kA lightning impulse residual voltage not more than kV (peak)	30/60 μ s 500A 操作冲击电流 残压不大于 kV (峰值)	30/60 μ s 500A switching impulse residual voltage not more than kV (peak)	2000 μ s 方波通流 容量 18 次 A (峰值)	Discharge capacity of rectangular wave 2000 μ s 18 times A (peak)	4/10 μ s 冲击大电流 2 次 kA (峰值)	4/10 μ s impulse high current 2 times kA (peak)	爬电 距离 mm	Creepage distance mm
YH10W2-96/250(238)	96				75		140	280/262	250/238	213/202										
YH10W2-100/260(248)	100		110		78		145	291/273	260/248	221/211										
YH10W2-102/266(253)	102				79.6		148	297/278	266/253	226/215										
YH10W2-108/281(268)	108				84		157	315/295	281/268	239/228										
YH10W2-192/500(476)	192				150		280	560/524	500/476	426/404										
YH10W2-200/520(496)	200				156		290	582/546	520/496	442/422										
YH10W2-204/532(506)	204			220	159		296	594/556	532/506	452/430										
YH10W2-216/562(536)	216				168.5		314	630/590	562/536	478/456										