NS-WY05 选型表

| NS- | 商标 | | | | | | | |
|-----------------------------|------------|----------|-----|-------|-------------------------------|----------------|----------------------|--|
| | 型号 | 产品名称 | | | | | | |
| | WY05 位移传感器 | | | | | | | |
| X- X:线性行程 单位: mm 例如: 1000mm | | | | | | 1000mm,2000mm, | | |
| | | | 代码 | 精度 | | | | |
| | | | 2 | 0.3% | | | | |
| | | | 3 | 0.2% | | | | |
| | | | 4 | 0.1% | | | | |
| | | | 5 | 0.05% | | | | |
| | | | | 代码 | 是否双向 | ij | | |
| | | | | L | 単向(艮 | 『零点在一 | 端,如:1000L 表示 1000mm) | |
| | | | | D | 双向(即零点在中间,如: 1000D 表示±1000mm) | | | |
| | | | | | 代码 | 输出信号 | | |
| | | | | | I | 4~20mA | | |
| | | | | | V1 | 0~5V | | |
| | | | | | V2 | 0~10V | | |
| | | | | | V3 | 0~±5V | | |
| | | | | | Т | 特殊规格 | | |
| | | | | | | 代码 | 工作电压 | |
| | | | | | | 1 | 12VDC | |
| | | | | | | 2 | 24VDC | |
| | | | | | | Т | 特殊规格 | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| NS- | WY05 | - 1000mi | m 3 | L | I | 2 | ◆ | |